

Overview

Cable pulley 90 with clamp 55.34

Product number: 04055034-1

Options

PU (Pcs)

1



Description

- **Application area:** Guiding and redirecting wire ropes in shading systems
- **Material:** Pulley made of impact-resistant plastic, bracket made of galvanized steel
- **Rope diameter:** Suitable for wire ropes up to 3 mm
- **Installation:** Screw-on mounting on square tubes (55 x 34 mm)
- **Special feature:** Precise mounting position through centered rope tension

The **Pulley 90 with bracket 55.34** is a reliable solution for guiding and redirecting wire ropes in shading systems. Its combination of impact-resistant plastic and galvanized steel ensures high stability and durability.

Thanks to its thoughtful design, the wire rope is automatically centered by the tension, ensuring a precise mounting position. The pulley is suitable for wire ropes up to 3 mm in diameter and can be screwed directly onto square tubes



TGU GmbH & Co. KG

Joseph-Monier Str. 2 48268
Greven

Tel.: 02575 - 955 87 0 Fax:

02575 - 955 87 87 email:
info@tgu-greven.com

HandelsregisterAmtsgericht

Steinfurt, HRB 31 56

Gerichtsstand Steinfurt

Erfüllungsort Greven DE

125 543 036

measuring 55 x 34 mm.

Mounting requires an M6 x 65 screw and an M6 nut, which must be ordered separately.

Note: Screws and nuts for mounting are not included in the delivery.