TGU GmbH & Co. KG
Joseph-Monier-Str. 2
48268 Greven
Deutschland

Kontakt:
Telefon: +49 2575/95587-15
Fax: +49 2575/95587-87
E-Mail: info@tgu-shop.com

Rechtliches:
Amtsgericht Ibbenbüren
USt-ID-Nr.:
DE 125543036

Overview

EWA 52.3505 Electric drive 350 Nm 4.4 rpm We06 400 V

Lock GmbH

Product number: 31147752



TGU GmbH & Co. KG
Joseph-Monier-Str. 2
48268 Greven
Deutschland

Kontakt:
Telefon: +49 2575/95587-15
Fax: +49 2575/95587-87
E-Mail: info@tgu-shop.com

Rechtliches:
Amtsgericht Ibbenbüren
USt-ID-Nr.:
DE 125543036

Description

- **Type:** EWA 52.3505 – Electric drive with worm gear
- **Model number:** 12528.3505.1205
- **Torque:** 350 Nm
- **Speed:** 4.4 rpm
- **Voltage:** 400 V, 3~ (three-phase AC), 50 Hz
- **Power:** 0.92 kW
- **Current consumption:** 1.60 A
- **Weight:** approx. 27.7 kg
- **Duty cycle:** S3–40%
- **Protection rating:** IP55
- **Temperature range:** –5 °C to +60 °C
- **Gear system:** Self-locking double worm gear
- **Limit switch:** END20.20 (integrated)
- **Shaft:** We06

The electric drive **EWA 52.3505**, model number **12528.3505.1205**, is designed for intermittent operation according to **duty cycle S3–40%**. It delivers a constant torque of **350 Nm** at a speed of **4.4 rpm** and operates on **400 V three-phase AC**.

The integrated **double worm gear** is self-locking, enabling secure positioning without backdriving.

The **We06 shaft**, with a length of **280 mm**, is built directly into the drive and is especially suitable for compact installations with limited space. It ensures reliable power transmission in minimal mounting space.

The **END20.20 limit switch** is **factory-integrated** and precisely matched to the motor. It enables accurate and safe end-position shutoff without additional installation effort.

With a **protection rating of IP55**, the drive is safeguarded against dust and water jets. The permissible ambient temperature range is between **–5 °C and +60 °C**.

This drive is ideal for greenhouse applications, particularly for controlling ventilation and shading systems.

Note: The EWA 52.3505 replaces the EWA 14.3505 (12214.3505.06).

TGU GmbH & Co. KG
Joseph-Monier-Str. 2
48268 Greven
Deutschland

Kontakt:
Telefon: +49 2575/95587-15
Fax: +49 2575/95587-87
E-Mail: info@tgu-shop.com

Rechtliches:
Amtsgericht Ibbenbüren
USt-ID-Nr.:
DE 125543036

Product information

Drive shaft:	Round shaft (06)
Phase(s):	3
Revolutions per minute:	4,4
Torque (Nm):	350
Voltage (V):	400