



TGU GmbH & Co. KG  
Joseph-Monier-Str. 2  
48268 Greven  
Deutschland

Kontakt:  
Telefon: +49 2575/95587-  
15  
Fax: +49 2575/95587-87  
E-Mail: info@tgu-shop.com

Rechtliches:  
Amtsgericht Ibbenbüren  
USt-ID-Nr.:  
DE 125543036

## Overview

# Tube motor RB40-11- 26\230\1\50\38\16 - 230V

Product number: 33100041



Erstellt am 21.04.2026.

Dieses Dokument stellt kein Angebot da. Es gelten die aktuellen Preise im Online-Shop.

All prices excl. VAT plus shipping costs and possible delivery charges, if not stated otherwise.



TGU GmbH & Co. KG  
Joseph-Monier-Str. 2  
48268 Greven  
Deutschland

Kontakt:  
Telefon: +49 2575/95587-  
15  
Fax: +49 2575/95587-87  
E-Mail: info@tgu-shop.com

Rechtliches:  
Amtsgericht Ibbenbüren  
USt-ID-Nr.:  
DE 125543036

## Description

- **Application:** Drive unit for sidewall and twin-roll screen systems in greenhouses (not suitable for roof roll screens)
- **Torque:** 40 Nm
- **Speed:** 11 rpm
- **Voltage:** 230 V, single-phase, 50 Hz
- **Power consumption:** 1.1 A
- **Tube diameter:** 50 mm aluminum sleeve (standard)
- **Limit switch:** Mechanical, precisely adjustable over 38 revolutions
- **Protection class:** IP44 – sealed against water ingress from the roll tube
- **Ridder Article No.:** 550018
- **Special features:**
  - Maintenance-free tubular motor with integrated planetary gear and motor brake
  - Thermal protection prevents overheating damage
  - Virtually silent operation
  - Suitable for intermittent operation (S3-6%, 4 min duty cycle)

The **RB40-11 tubular motor** is a compact and powerful drive unit for roll screen systems in glass and film greenhouses. Thanks to its precise limit switch, robust construction, and quiet performance, it is ideal for medium-duty applications. The integrated 50 mm aluminum sleeve allows for space-saving installation, while the IP44 protection rating prevents moisture ingress—ensuring long-lasting and reliable operation.