

Overview

Pulley 40 (TGU) with splint bracket - PU = 100 pcs

Product number: 01500300

Options

PU (Pcs)



Image

Image





TGU GmbH & Co. KG
Joseph-Monier-Str. 2
48268 Greven
Deutschland

Kontakt:
Telefon: +49 2575/95587-
15
Fax: +49 2575/95587-87
E-Mail: info@tgu-shop.com

Rechtliches:
Amtsgericht Ibbenbüren
USt-ID-Nr.:
DE 125543036

Description

- **Application area:** Guide roller for already tensioned cables
- **Material:** High impact resistant plastic
- **Diameter:** 40 mm
- **Compatibility:** Suitable for cables up to 7 mm in diameter
- **Axle:** Made of stainless steel
- **Installation:** Split bracket enables attachment to tensioned cables
- **Special feature:** Can be rotated and suspended via included S-hook to divert cables

This **plastic pulley with split bracket** is designed as a guide roller for pre-tensioned cables. Its split bracket allows it to be mounted directly onto already strained cables without disassembly. When rotated, the pulley can be suspended using the included **S-hook**, allowing it to divert cable paths effectively.

Made of **high-impact plastic** with a **stainless steel axle**, the pulley offers both durability and weather resistance. With a compact diameter of **40 mm**, it accommodates wire cables up to **7 mm** and is well-suited for flexible mounting and cable management in greenhouse shading or mechanical systems.